BX-V070-120V




Characteristics

Over/under voltage protector: When the voltage exceeds the limit, it will automatically cut off the power to prevent the electrical appliances being damaged by the too low or too high voltage.


Adjustable threaded bolt: Users can adjust the high/low voltage and delay time to meet their needs.

Visual window: real-time display of product working status, eye-catching.

Flame retardant material: Be able to reach the experimental standards of level test of UL94-5VA..



Introduce



tion	\bullet	Working voltage/F	requency:120VAC/50HZ-60
	${ \bullet }$	Under voltage:	90VAC
ator	${ \bullet }$	Over voltage:	140VAC
	${ \bullet }$	working current:	15A
	${ \bullet }$	Maximum power:	1800W
	${ \bullet }$	Delay Time:	3min/5s
	${ \bullet }$	Warranty time:	1 year
	${ \bullet }$	work environment	: −5°C~+55°C
	${ \bullet }$	weight:	160g
	${ \bullet }$	Product size:	77*36*123mm
	${ \bullet }$	Shell material:	PC
	lacksquare	Outer box size:	48*47*37cm
XX7.	~ ~*		

■Warning

*The total power of connected electrical equipment shall not exceed the rated power.

*Do not use this product in damp or not ventilated environment.

*Non-professionals do not open, change, repair the product.

*Poor connection of the front terminal or poor connection of the plug may

cause a danger.

*Prohibition of combustion and keep away from fire.

